



PATIO DOOR

PERFORMANCE CHART



LUX Windows 800-Series Sliding Glass Door

✓ Frame

- 4 - 9/16” brickmold frame depth
- 1 - 1/4” nailfin setback
- J-Pocket for simplified siding installation
- Exterior style lines and grooves
- Removable panel and screen roller tracks
- Exterior-glazed fixed glass

✓ Panel

- Exterior glazed sash glass
- 7/8” glazing leg height
- Dual - weatherstripped integral interlocks
- Interior thumb lock
- Fully reinforced vinyl components
- Smooth and adjustable rollers

✓ Glass

- E366 low - E and clear insulated glass units
- Argon enhanced to improve insulation performance
- 5 - year warranty

NAFS Product Performance

Product Type	Test Unit Size (Inches)	Overall Rating	Air Infiltration	Water Pressure (psf)	Structural Pressure (psf)	U-Factor	Solar Heat Gain Coefficient*	Test Standard	AAMA 1704 Egress Rated
OX/XO Sliding Door	72 X 77	DP45	0.19	7.52	75.19	0.30	0.22	NAFS17	Yes
	72 X 80	DP45	0.19	7.52	75.19	0.30	0.22	NAFS17	Yes

* SHGC established without window grids. Adding grids subtracts 0.02 from each SHGC value.