



WINDOW SPECS

LUX Windows 700-Series Window



✓ Frame

- 2-7/8” brickmold frame depth
- 1-1/2” beveled frame depth
- Exterior style lines and grooves
- Pocket sill water management system
- Smooth spring-coil balancers
- Exterior-glazed fixed glass

✓ Sash

- Exterior glazed sash glass
- Tilt-in sash for easy exterior cleaning
- Recessed easy-open tilt latches
- Fully reinforced top rail and stiles

✓ Glass

- E366 low-E and clear insulated glass units
- Argon enhanced to improve insulation performance
- Single strength, double strength, tempered, and obscure options
- 5-year warranty

NAFS Product Performance									
Product Type	Test Unit Size (Inches)	Overall Rating	Air Infiltration	Water Pressure (psf)	Structural Pressure	U-Factor	Solar Heat Gain Coefficient*	Test Standard	AAMA 1704 Egress Rated
Single Hung	14 X 40	DP50	≤ 0.30	7.52	75.19	0.30	0.23	NAFS17	
	14 X 60	DP50	≤ 0.30	7.52	75.19	0.30	0.23	NAFS17	
	24 X 30	DP50	≤ 0.30	7.52	75.19	0.30	0.23	NAFS17	
	24 X 35	DP50	≤ 0.30	7.52	75.19	0.30	0.23	NAFS17	
	24 X 36	DP50	≤ 0.30	7.52	75.19	0.30	0.23	NAFS17	
	24 X 42	DP50	≤ 0.30	7.52	75.19	0.30	0.23	NAFS17	
	24 X 48	DP50	≤ 0.30	7.52	75.19	0.30	0.23	NAFS17	
	30 X 27	DP50	≤ 0.30	7.52	75.19	0.30	0.23	NAFS17	
	30 X 30	DP50	≤ 0.30	7.52	75.19	0.30	0.23	NAFS17	
	30 X 32	DP50	≤ 0.30	7.52	75.19	0.30	0.23	NAFS17	
	30 X 36	DP50	≤ 0.30	7.52	75.19	0.30	0.23	NAFS17	
	30 X 40	DP50	≤ 0.30	7.52	75.19	0.30	0.23	NAFS17	
	30 X 48	DP50	≤ 0.30	7.52	75.19	0.30	0.23	NAFS17	
	30 X 54	DP50	≤ 0.30	7.52	75.19	0.30	0.23	NAFS17	
	30 X 60	DP50	≤ 0.30	7.52	75.19	0.30	0.23	NAFS17	
	32 X 42	DP50	≤ 0.30	7.52	75.19	0.30	0.23	NAFS17	
	32 X 60	DP50	≤ 0.30	7.52	75.19	0.30	0.23	NAFS17	
	36 X 35	DP50	≤ 0.30	7.52	75.19	0.30	0.23	NAFS17	
	36 X 36	DP50	≤ 0.30	7.52	75.19	0.30	0.23	NAFS17	
	36 X 40	DP50	≤ 0.30	7.52	75.19	0.30	0.23	NAFS17	
	36 X 54	DP50	≤ 0.30	7.52	75.19	0.30	0.23	NAFS17	Yes
Drywall Single-Hung	36 X 60	DP50	≤ 0.30	7.52	75.19	0.30	0.23	NAFS17	Yes
	36 X 72	DP50	≤ 0.30	7.52	75.19	0.30	0.23	NAFS17	Yes
Picture Window	40 X 60	DP30	≤ 0.30	4.51	45.11	0.30	0.23	NAFS17	Yes
	46 X 54	DP30	≤ 0.30	4.51	45.11	0.30	0.23	NAFS17	Yes
	46 X 60	DP30	≤ 0.30	4.51	45.11	0.30	0.23	NAFS17	Yes
	18 X 18	DP65	<0.01	9.78	97.75	0.27	0.25	NAFS17	
	24 X 8	DP65	<0.01	9.78	97.75	0.27	0.25	NAFS17	
	24 X 24	DP65	<0.01	9.78	97.75	0.27	0.25	NAFS17	
	24 X 36	DP60	<0.01	9.02	90.23	0.27	0.25	NAFS17	
	24 X 48	DP50	<0.01	7.52	75.19	0.27	0.25	NAFS17	
	24 X 54	DP50	<0.01	7.52	75.19	0.27	0.25	NAFS17	
	30 X 8	DP65	<0.01	9.78	97.75	0.27	0.25	NAFS17	
	30 X 10	DP65	<0.01	9.78	97.75	0.27	0.25	NAFS17	
	30 X 12	DP65	<0.01	9.78	97.75	0.27	0.25	NAFS17	
	30 X 14	DP65	<0.01	9.78	97.75	0.27	0.25	NAFS17	
	30 X 18	DP65	<0.01	9.78	97.75	0.27	0.25	NAFS17	
	30 X 40	DP60	<0.01	9.02	90.23	0.27	0.25	NAFS17	
	30 X 48	DP50	<0.01	7.52	75.19	0.27	0.25	NAFS17	
	30 X 72	DP40	<0.01	6.02	60.15	0.27	0.25	NAFS17	
	36 X 8	DP65	<0.01	9.78	97.75	0.27	0.25	NAFS17	
	36 X 12	DP65	<0.01	9.78	97.75	0.27	0.25	NAFS17	
	36 X 14	DP65	<0.01	9.78	97.75	0.27	0.25	NAFS17	
	36 X 35	DP60	<0.01	9.02	90.23	0.27	0.25	NAFS17	
	36 X 40	DP60	<0.01	9.02	90.23	0.27	0.25	NAFS17	
	36 X 42	DP50	<0.01	7.52	75.19	0.27	0.25	NAFS17	
	36 X 48	DP50	<0.01	7.52	75.19	0.27	0.25	NAFS17	
	36 X 72	DP40	<0.01	6.02	60.15	0.27	0.25	NAFS17	
	40 X 8	DP65	<0.01	9.78	97.75	0.27	0.25	NAFS17	
	46 X 14	DP65	<0.01	9.78	97.75	0.27	0.25	NAFS17	
	58 X 12	DP45	<0.01	6.77	67.67	0.27	0.25	NAFS17	
	60 X 14	DP45	<0.01	6.77	67.67	0.27	0.25	NAFS17	
	72 X 8	DP45	<0.01	6.77	67.67	0.27	0.25	NAFS17	
	72 X 12	DP45	<0.01	6.77	67.67	0.27	0.25	NAFS17	
	72 X 14	DP45	<0.01	6.77	67.67	0.27	0.25	NAFS17	

* Value established without window grids. Adding grids subtracts 0.02 from each SHGC value.