

Product data sheet

Specifications

SQUARE D



Contactor, Definite Purpose, 75A, 3 pole, 40 HP at 575 VAC, 3 phase, 110/120 VAC 50/60 Hz coil, open

8910DPA73RV02

Product availability: Stock - Normally stocked in distribution facility

Main

Product or Component Type	Definite Purpose Contactor
Line Rated Current	75 A
Number of Poles	3P
Pole contact composition	3 NO
Range of Product	DPA

Complementary

Maximum Horse Power Rating	5 hp 115 V AC, 1 phase 15 hp 230 V AC, 1 phase 25 hp 230 V AC, 3 phase 40 hp 460 V AC, 3 phase 40 hp 575 V AC, 3 phase
Locked rotor rated current	450 A 277 V AC 375 A 460 V AC 300 A 575 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Phase	3 phase
Electrical Connection	Quick connect terminals Box lugs
Height	3.7 in (92.8 mm)
Width	4.10 in (104.03 mm)
Depth	2.6 in (65 mm)

Environment

Product Certifications	UL Recognized CSA
------------------------	----------------------

Ordering and shipping details

Category	US1CP1B21347
Discount Schedule	CP1B
GTIN	785901768333
Returnability	Yes
Country of origin	CN

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	4.06 in (10.3 cm)
Package 1 Width	3.35 in (8.5 cm)
Package 1 Length	3.66 in (9.3 cm)
Package weight(Lbs)	24.0 oz (680.4 g)

Contractual warranty

Warranty	18 months
----------	-----------


Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.


[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions

Use Again

 Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No

Technical Illustration

Wiring diagram

