

Description: 14 AWG 2/C STR OAS CMP-CL2P  
Specifications: UL Standards 13 & 444; NEC Articles 725 & 800

**Construction:**

Conductor 14 AWG 19/.0147 Stranded Bare Copper  
Insulation Plenum PVC  
Insulation Thickness 0.007" nom.  
Insulation Colors Blk,Red  
Insulation Diameter 0.089 nom.  
Lay Length 3.25" nom.  
Drain Wire 24 7/32 TC  
Shield 0.001" Thick Aluminum/Mylar

Jacket Plenum PVC  
Color Natural  
Jacket Thickness 0.016" nom.  
Outside Diameter 0.214" nom.  
Legend (Ink Print)

HONEYWELL P/N 3223 2C14 SHIELDED 3038058 (ETL) CL2P OR CMP C(ETL)US FT6  
(RoHS) W/O# XXXXXX-XXXXXX XXXXX FT DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9

**Properties**

Temperature Rating -20 to 60 °C  
Operating Voltage 300 Volts max.  
Capacitance 72 pf/ft nom.  
Impedance 28 Ohms nom.  
DC Resistance 2.6 Ohms/M' at 20°C  
Flame Rating UL 910, NFPA 262, CSA FT6