



1PL2/03, UV Rated Black, 1-sided, 3-port, #14-2/0 AWG

By Burndy
Catalog # 1PL2/03

UV Rated Black UNITAP™ Connector; PL = Single Sided Entry; PLO = Offset Entry



Features

- UV Rated Covering over AL6061-T6 aluminum body saves time, lowering installation costs and eliminates taping
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces the number of connectors necessary to carry in inventory

Application

For Indoor Use Only, Copper Or Stranded Aluminum

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Buy America(n) Qualified	Buy America Compliant (All status valid till December 2025)
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	No

Conductor

Conductor - Copper Str Size	<ul style="list-style-type: none"> • 14 AWG • 12 AWG • 10 AWG • 9 AWG • 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 • 2/0 AWG
Conductor - AL Str Size	<ul style="list-style-type: none"> • 14 AWG • 12 AWG • 10 AWG • 9 AWG

- 8 AWG
- 7 AWG
- 6 AWG
- 5 AWG
- 4 AWG
- 3 AWG
- 2 AWG
- 1 AWG
- 1/0
- 2/0 AWG

Conductor - AL Str Size Range	14 AWG - 2/0 AWG
Conductor Size	14-2/0 AWG
Conductor - Copper Str Size Range	14 AWG - 2/0 AWG
Conductor Type	<ul style="list-style-type: none"> • AL C Str-Size • CU C Str-Size

Configuration

Physical Attribute - Number of Screws	3
Connector Type	Multi Tap
Number Of Ports	3

Current

Voltage - Maximum	600 V
-------------------	-------

Dimensions

Dimension - L Length Overall mm	56 mm
Dimension - Height fraction	1.375 in
Dimension - Height inch	1.38 in
Dimension - Height mm	35.1 mm
Dimension - Screw Size inch Width	7/16
Dimension - Width fraction	1.31 in
Dimension - Width inch	1.31 in
Dimension - Width mm	33 mm
Length	2.19 in
Dimension - Length Overall inch	2.19 in
Height	1.38 in
Dimensions	2.19 in x 1.31 in x 1.38 in

Force Related

Installation Torque
Recommended in-lb

120 in-lb

Plating Type
UPC

Unplated
781810286845

General

Material - Hardware Aluminum
Insulation Type Plastisol
Trade Name UNITAP™
Insulation Y
Sub Brand UNITAP
Plated N
Type BIBS, Multi-Port
UPC 12 Digit 781810286845
UPC 14 Digit GTIN 00781810286845
Material Aluminum
Hex Key 3/16

Logistics

Minimum Pack Quantity 1
Carton Quantity 100
Pallet Quantity 6400

Operational

Temperature Rating 194° F

Product Assets

[Catalog \[English\]](#)
[Catalog \[English\]](#)



A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved
BRDY-1PL203-SPEC-EN | REV 11/2025