



Family

Catalog Number: PACOF-29B.50
Product ID: 7TAA292730R0008
UPC Number: 78620999802
EAN Number: 07630030270505
Status: Active

Divisible Flexible Black Conduit, (PACO) Material - Polyamide 6, Conduit Size NW - 29, 50 Meters

- Can be opened and closed again in longitudinal directional any time
- PMA standard nominal widths can be used in combination with all PMA fittings
- Easy installation
- Trouble-free retrofitting
- Self-extinguishing
- Free from halogens and cadmium
- Vehicle Building

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5535 Electrical conduit
Brand Name	PMA
Type	Divisible Conduit
Application	Machine
Trade Size	NW29
Length	50 m
Flexibility	Medium Flexibility
Material	Polyamide/Nylon 6
Color	Black

European Specifications (ETIM)

ETIM	EC001175 Corrugated plastic hose
Nominal diameter	32mm
Outer diameter	34.5mm
Inner diameter	27.2mm
Material	Polyamide 6
Compressive strength	180N
Operating temperature	-40 - +105°C
Fire resistance in accordance with UL94	V0
UV resistant	Y
Colour	Black
Sheathing material	Not sheathed
Bending strength	Flexible
Lengthwise slotted	N
Closable (two-part)	Y
Halogen free	Y
Approved according to DIN EN 61386-23	N
Approved according to UR	N
Approved according to CSA	N
Approved according to LUL/British Standard	N
Approved according to Lloyd's Register TA	N
Approved according to UTAC	N
Approved according to DIN 5510	N
Approved according to NF F 16-101	N

Packaging

Inner Quantity	1
Outer Quantity	5
Outer Dimensions (inches)	47.244x31.496x30.709
Weight Uom	18.5 lbs. Each

Documents / Support Tools

Technical Drawing / Data Sheet Canada	Available on Website
Video US	Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com