

## YS36, Cu Compression Splice, Long Barrel, 600 kcmil

By Burndy  
Catalog # [YS36](#)



600 kcmil, CU, Long Barrel SPLICE

### Features

- Copper seamless barrel with center stop indentations to indicate when wire is fully inserted into each side of the barrel
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors clearly marked with color coding

### Application

Wire Splice

### Specifications

Buy American Compliant	No
EU RoHS Indicator	Yes
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

### Conductor

Conductor - Material	COPPER
Wire Size	600 kcmil
Conductor - Copper Str Size	600 kcmil
Conductor Size	600 KCMIL
Conductor - Copper Str Size Range	600 kcmil
Conductor Type	CODE

### Configuration

Connector Type	LONG BARREL
----------------	-------------

### Current

Voltage - Maximum	35000
Voltage Rating	35 kV

### Dimensions

Dimension - L Length Overall mm	149 mm
Dimension - Strip Length inch	2-11/16
Dimension - B Length inch	2.63 in
Dimension - Length Overall inch	5.85 in

### General

Die Index	22
Trade Name	HYLINK™
Sub Brand	HYLINK
Color Code	Green
Plated	Y
Feature - Barrel Type	Long
Feature - Barrel Style	Chamfered
Type	YS, Long Barrel
UPC 12 Digit	781810526255
UPC 14 Digit GTIN	00781810526255
Material	COPPER
Plating Type	Tin - Electro Plated
Finish Type	Tin-Plated
UPC	781810526255

### Logistics

Minimum Pack Quantity	1
Carton Quantity	6

### Product Assets

[Catalog \[English\]](#)