



# LED Lamps - HID



## Selectable ED17

Current's LumenChoice® + SpectraChoice™ selectable ED17 offers unmatched flexibility in a single lamp, and features built-in switches to change wattage and color temperature, no tools required.



### PERFORMANCE HIGHLIGHTS:

#### Selectable ED17 HID Replacement Lamp

**Light Output:** 3,400 / 5,500 / 7,000 Lumens

**CRI:** 70

**Selectable CCT:** 1800K / 2200K / 2700K  
3000K / 4000K / 5000K

**Input Voltage:** 120-277V; 120-347V

**Efficiency:** Up to 161 LPW

**Selectable Wattage:** 21W / 35W / 45W

**Life:** 50,000 hours L70

**Temperature Rating:** -40°C to 50°C

**Location Rating:** Damp; Open or Enclosed

### LIMITED WARRANTY

5 years

### FEATURES:

- Three wattage levels and three color temperature levels that can be adjusted with built-in switches, no tool required
- E26-to-EX39 socket adapter included to maximize flexibility
- Operates from 120-277VAC input voltage (ballast bypass)
- Matches ANSI length & diameter for equivalent HID lamp shape
- Lasts up to 4x longer than HID
- These lamps are energy efficient, contain no lead or mercury and are compliant with material restriction requirements of RoHS

### BENEFITS:

- Optimize light levels and power consumption instantly for each application, maximizing energy savings immediately
- Use one lamp for many applications, simplifying project management by streamlining BOMs
- One lamp can replace many, greatly reducing inventory
- Compact size & omnidirectional light output allow single lamp to be used in wide variety of fixtures
- Eliminates the need for ballasts

### LEARN MORE:

To learn more about saving money and energy, go to [www.LED.com](http://www.LED.com).



Selectable **LED Lamps**

### Do more with less.


- *Reduce Inventory*
- *Simplify Projects*
- *Optimize Solutions*



## Selectable ED17

CUSTOMER NAME \_\_\_\_\_  
 PROJECT NAME \_\_\_\_\_  
 DATE \_\_\_\_\_ NOTES \_\_\_\_\_

### Selectable LumenChoice® + SpectraChoice™ ED17 HID Replacement - Type B

Bulb Shape	Base Type	Order Code	Description	Volts	Carton Qty <sup>2</sup>	MOL (in)	MOD (in)	Selectable Watts*	Selectable Lumens (Initial)*	Selectable Color Temp. (Initial)*	Wattage Replacement <sup>5</sup>	CRI	Rated Life L70 (Hrs) <sup>1</sup>	DLC <sup>3</sup>	Location Rating <sup>4,5</sup>	
<b>LED Replacement Lamp for HID - Ballast Bypass (Type B)</b>																
	E26/EX39	93303384	LED/LC/ED17/7SC	120-277	3	5.4	2.6	21	3,400	3000K	50W HPS / 70W MH	>70	50,000	-	Damp	
								35*	5,500*	4000K*	70W HPS / 100W MH					
								45	7,000	5000K	100W HPS / 175W MH					
								21	3,400	3000K	50W HPS / 70W MH	>70	50,000	-	Damp	
								35*	5,500*	4000K*	70W HPS / 100W MH					
								45	7,000	5000K	100W HPS / 175W MH					

### Warm Selectable LumenChoice® + SpectraChoice™ HID Replacement - Type B

Bulb Shape	Base Type	Order Code	Description	Volts	Carton Qty <sup>2</sup>	MOL (in)	MOD (in)	Selectable Watts*	Selectable Lumens (Initial)*	Selectable Color Temp. (Initial)*	Wattage Replacement <sup>5</sup>	CRI	Rated Life L70 (Hrs) <sup>1</sup>	DLC <sup>3</sup>	Location Rating <sup>4,5</sup>	
<b>LED Replacement Lamp for HID - Ballast Bypass (Type B)</b>																
ED17	E26/EX39	93315986	LED/LC/ED17/7WSC/120-347	120-347	3	5.4	2.6	21	2,450	1800K	35W HPS / 50W MH	>70	50,000	-	Damp	
									3,000	2200K	35W HPS / 50W MH					
									3,300	2700K	50W HPS / 50W MH					
									3,950	1800K	35W HPS / 50W MH					
									4,900*	2200K*	50W HPS / 70W MH					
									5,350	2700K	70W HPS / 70W MH					
									4,900	1800K	50W HPS / 70W MH					
									45	6,200	2200K					70W HPS / 70W MH
										6,650	2700K					70W HPS / 100W MH

<sup>1</sup> The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original lumen output (L70)

<sup>2</sup> Minimum order quantity = 1

<sup>3</sup> E26 based products are not eligible for DLC. Not all product variations on this page are DLC qualified. Visit [qpl.designlights.org/solid-state-lighting](http://qpl.designlights.org/solid-state-lighting) to confirm qualification.


<sup>4</sup> UL 1993 Environmental Requirements for LED LAMPS

Damp Location - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to electrical equipment, including partially protected locations

<sup>5</sup> Not suitable for air-tight explosive or hazardous fixtures.

<sup>6</sup> Wattage Replacement levels correspond with wattage levels. Wattage Replacements based on NEMA Standards Publication LL 10-2020 *Replacing HID Lamps with LED Lamps: Light Output Equivalency Claims*.

\* Default wattage and color temperature settings noted by "\*" in tables above.



Select color temperature using built-in switch.



Select wattage (lumens) using built-in switch.

