

Product data sheet

Characteristics

SSP02XDSE20A1

Surge protection device, XDSE, 200kA,
208Y/120 VAC, 3 phase, 4 wire, SPD type 1



Main

Product	Surge protection device
---------	-------------------------

Complementary

Voltage Rating	208Y/120 V AC
MCOV	150 V
Surge Current	200 A per phase
Voltage Protection Rating	700 V L-N 700 V L - G 600 V L - L 1000 V N - G
Rated Current	20 kA
Number of Phases	3 phase
Wiring Configuration	4-wire
Height	6.0 in (152 mm)
Width	6.0 in (152 mm)
Depth	4.0 in (101 mm)

Environment

Enclosure Rating	NEMA 4X
------------------	---------

Ordering and shipping details

Category	US1DE1B08466
Discount Schedule	DE1B
GTIN	785901987383
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.0 in (15.2 cm)
Package 1 Width	6.0 in (15.2 cm)
Package 1 Length	4.0 in (10.1 cm)
Package 1 Weight	3.979 lb(US) (1.805 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes