

# Product data sheet

Specifications



## Socket-outlet, X Series, 20A, decorator, GFCI, tamper resistant, commercial, white, matte finish

SQR51201WH

**Product availability: Stock - Normally stocked in distribution facility**

### Main

Range	Square D X Series
Product or Component Type	Socket-outlet
Aesthetic name	X Series
Device Application	Power supply
Device presentation	Mechanism with fixing frame
Body type	Decorator
Socket number	2
Outlet poles configuration	2P + E
Outlet standard	NEMA
Socket additional information	Tamper resistant

### Complementary

Device mounting	Flush
Mounting Mode	By screws
[Ie] rated operational current AC	20 A
[Ue] rated operational voltage	125 V
Network type	AC
Network Frequency	60 Hz
Number of gangs	1 gang
Number of modules	1
Color	White
Surface Finish	Matte
Material	Plastic: strap Metal: fixing frame
Connections - terminals	Phase and neutral 4 screw terminal copper Earth 1 screw terminal copper
Earth circuit	Self earthing
Protection Type	GFCI
Width	1.7 in (42 mm)
Height	4.06 in (103 mm)
Depth	1.6 in (41 mm)
Quantity per Set	1 piece

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Environment

Product Certifications	cULus
Standards	UL 498 UL 943 ICES-003

## Ordering and shipping details

Category	US10DE909932
Discount Schedule	0DE9
GTIN	785901544920
Returnability	Yes
Country of origin	CN

## Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.900 in (4.826 cm)
Package 1 Width	2.100 in (5.334 cm)
Package 1 Length	4.400 in (11.176 cm)
Package weight(Lbs)	5.600 oz (158.757 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	4.250 in (10.795 cm)
Package 2 Width	4.750 in (12.065 cm)
Package 2 Length	9.300 in (23.622 cm)
Package 2 Weight	3.750 lb(US) (1.701 kg)
Unit Type of Package 3	CAR
Number of Units in Package 3	60
Package 3 Height	11.100 in (28.194 cm)
Package 3 Width	7.200 in (18.288 cm)
Package 3 Length	17.800 in (45.212 cm)
Package 3 Weight	22.000 lb(US) (9.979 kg)

## Contractual warranty

Warranty	2 years
----------	---------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

Yes

[EU RoHS Directive](#)

Compliant

REACH Regulation

[REACH Declaration](#)

California proposition 65

**WARNING:** This product can expose you to chemicals including: carbon black, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## Use Again

### Repack and remanufacture

[Circularity Profile](#)

[End of Life Information](#)


Take-back

No


Technical Illustration

Wiring diagram

A: One cable (2 or 3 wires) entering the box



OR B: Two cables (4 to 6 wires) entering the box



About Wire Connections:





Image of product / Alternate images

Alternative

---

