

Product data sheet

Specifications



Switch disconnecter, TeSys Control, for ON/emergency stop, 63A, 4 screws fixing, for mounting at back of an enclosure

VCCF3

Product availability: Stock - Normally stocked in distribution facility

Main

Range	TeSys
Product Name	TeSys VARIO
Device Short Name	VCCF
Product Type	Emergency stop switch disconnecter

Complementary

Device Composition	Switch Handle Shaft extension
Mounting Support	Handle door Switch symmetrical rail Switch plate
Mounting Method	By 4 screws handle By clips switch By screws switch
Performance Level	High performance
Number of Poles	3P
Contact Type and Composition	3 NO
[Ue] IEC Rated Operational Voltage	690 V AC 50/60 Hz
IEC Rated Operational Power in W	11 kW 230...240 V AC-3) 22 kW 500 V AC-3) 22 kW 690 V AC-23A) 30 kW 500 V AC-23A) 18.5 kW 400...415 V AC-3) 18.5 kW 690 V AC-3) 15 kW 230...240 V AC-23A) 22 kW 400...415 V AC-23A)
[Ie] Rated Operational Current	41.5 A AC-23 Ue: 400 V
[Ith] Conventional Free Air Thermal Current	63 A
[Ithe] Conventional Enclosed Thermal Current	50 A
Making Capacity (I Rms)	630 A 400 V AC-21A 630 A 400 V AC-22A 630 A 400 V AC-23A
Breaking Capacity	500 A 400 V AC-21A) 500 A 400 V AC-22A) 500 A 400 V AC-23A)
Rated Conditional Short Circuit Current	10 kA 400 V 63 A aM 10 kA 400 V 63 A gG

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

[Icm] Rated Short Circuit Making Capacity	2.1 kA 400 V at I _{peak}
[Icw] Rated Short Time Withstand Current	756 A 400 V 1 s
[Uimp] Rated Impulse Withstand Voltage	8 kV
Suitability for Isolation	Yes
Network Type	DC AC
Intermittent Duty Class	30
Control Type	Rotary handle
Rotary Handle Mounting Style	Extended
Handle Color	Red
Handle Front Plate Color	Yellow
Rotary Handle Padlocking	1 to 3 padlocks 0.2...0.3 in (4...8 mm)
Marking	0 - 1
Mechanical Durability	30000 cycles
Electrical Durability	30000 cycles AC-21 30000 cycles DC-1...5
IEC Terminal Connection	Power circuit screw clamp terminals 0.04 in ² (25 mm ²) solid Power circuit screw clamp terminals 0.02 in ² (16 mm ²) flexible - with cable end
Tightening Torque	Power circuit 35.4 lbf.in (4 N.m) screw clamp terminals
Base Dimension	60 x 60 mm
Height	3.3 in (83 mm)
Width	2.4 in (60 mm)
Product Weight	0.97 lb(US) (0.44 kg)

Environment

Standards	IEC 60947-3
Product Certifications	UL CCC GL CSA UKCA
Degree of Protection	IP20 conforming to IEC 60529 IP65
Protective Treatment	TC
Mechanical Robustness	Vibrations 10...150 Hz 1 gn) IEC 60068-2-6 Shocks 11 ms 30 Gn) IEC 60068-2-27
Ambient Air Temperature for Operation	-4...122 °F (-20...50 °C)
Fire Resistance	1760 °F (960 °C) IEC 60695-2-1
Compatibility Code	Main switch disconnecter

Ordering and shipping details

Category	US10CP121730
Discount Schedule	0CP1
GTIN	3389110194005
Returnability	Yes

Country of origin	CZ
-------------------	----

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Nbr. of units in pkg.	1
-----------------------	---

Package 1 Height	11.614 in (29.500 cm)
------------------	-----------------------

Package 1 Width	4.528 in (11.500 cm)
-----------------	----------------------

Package 1 Length	3.819 in (9.700 cm)
------------------	---------------------

Package weight(Lbs)	20.106 oz (570.000 g)
---------------------	-----------------------

Unit Type of Package 2	P06
------------------------	-----

Number of Units in Package 2	55
------------------------------	----

Package 2 Height	29.528 in (75.000 cm)
------------------	-----------------------

Package 2 Width	23.622 in (60.000 cm)
-----------------	-----------------------

Package 2 Length	31.496 in (80.000 cm)
------------------	-----------------------

Package 2 Weight	106.505 lb(US) (48.310 kg)
------------------	----------------------------

Contractual warranty

Warranty	18 months
----------	-----------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 33

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number 63dc4fbe-3f44-4801-881b-22a3bb8008d9

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov**

PVC free Yes

Use Again

Repack and remanufacture

Circularity Profile No need of specific recycling operations

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.