

Main

Range of Product	PowerPacT H PowerPacT J PowerPacT L
Product or Component Type	Shunt trip

Complementary

Rated voltage	24 V AC
Tightening torque	12.4 lbf.in (1.4 N.m) 0.001...0.004 in ² (0.82...2.5 mm ²) (AWG 18...AWG 14)

Environment

Product Certifications	CSA
------------------------	-----

Ordering and shipping details

Category	US10DE201103
Discount Schedule	0DE2
GTIN	3606485955773
Returnability	Yes
Country of origin	PL

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.800 in (4.572 cm)
Package 1 Width	4.200 in (10.668 cm)
Package 1 Length	5.700 in (14.478 cm)
Package 1 Weight	5.280 oz (149.685 g)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.