


<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

Driver Info		LED Info	
Type	Constant Current	Watts	12W
120V	0.11A	Color Temp	2700K/3000K/3500K/4000K/5000K
208V	N/A	Color Accuracy	90 CRI
240V	N/A	L70 Lifespan	50,000 Hours
277V	N/A	Lumens	850 lm
Input Watts	12W	Efficacy	75

### Technical Specifications

<p><b>Performance</b></p> <p><b>Description:</b> This 5-inch canless wafer downlight has an ultra low-profile design making them a flexible solution for both new construction and retrofit applications. The remote driver box has quick connectors, knockouts, and plenty of space for daisy chain wiring or adding an emergency backup unit.</p> <p><b>Product Type:</b> Recessed Downlights</p> <p><b>Input Wattage:</b> 12W</p> <p><b>Lumens:</b> 850lm</p> <p><b>L70 Lifespan:</b> 50,000-Hour LED lifespan based on IES LM-70 results</p> <p><b>Dimming:</b> Yes, See Dimmer Compatibility List</p> <p><b>Compliance</b></p> <p><b>UL Listed:</b> Suitable for wet locations</p>	<p><b>NEC Compliant:</b> Suitable for use in closets. Compliant with NEC Sec. 410.16 (A)(1) and 410.16 (C3).</p> <p><b>Trade Agreements Act Compliant:</b> This product is a product of Cambodia and a "designated country" end product that complies with the Trade Agreements Act</p> <p><b>Electrical</b></p> <p><b>THD:</b> ≤20%</p> <p><b>Power Factor:</b> ≥0.9</p> <p><b>Operating Frequency:</b> 60 Hz</p> <p><b>Operating Temperature Range:</b> -30°C to 40°C</p> <p><b>Construction</b></p> <p><b>Material:</b> Plastic</p> <p><b>Trim Style:</b> Baffle</p> <p><b>Shape:</b> Round</p>	<p><b>Mounting:</b> Recessed ceiling</p> <p><b>Other</b></p> <p><b>Warranty:</b> RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <a href="http://rablighting.com/warranty">rablighting.com/warranty</a>.</p> <p><b>Buy American Act Compliance:</b> RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.</p>
---	--	--

## Dimensions



## Features

- 5 color temperatures in 1 SKU (2700K, 3000K, 3500K, 4000K, 5000K)
- Super slim Edge-lit fixture for thin fixture depth
- No recessed housing or J-box required
- New construction or retrofit applications
- UL wet location rated
- Smooth diffused uniform light distribution
- Dimmable down to 10% on compatible dimmers
- Spring loaded retention clips
- Robust, die cast aluminum construction
- IC and airtight rated
- 5-Year, No-Compromise Warranty

## Ordering Matrix

Family	Size	Shape	Wattage	CRI/Color Temp	Voltage	Finish	Trim	Depth
WFRL	5	R	12	9CCT	120	W	B	
	4 = 4"	R = Round	13 = 13W	9FA = 90 CRI, 2700K/3000K/3500K/4000K/5000K CCT	120 = 120V	W = White	B = Baffle	Blank = Standard
	5 = 5"	S = Square	23 = 23W	Adjustable	D = 120V/277V		S = Smooth	S = Shallow
	6 = 6"		14 = 14W	9CCT = 90 CRI, 2700K/3000K/3500K/4000K/5000K CCT				
	8 = 8"		12 = 12W	Adjustable				
	3 = 3"		10.5 = 10.5W					
			9 = 9W					
			6 = 6W					