

Product data sheet

Characteristics

8910DPA53V06

Contactor, Definite Purpose, 50A, 3 pole, 30HP at 575VAC, 3 phase, 440/480VAC 50/60Hz coil, open



Main

Product or Component Type	Definite Purpose Contactor
Line Rated Current	50 A
Number of Poles	3P
Pole contact composition	3 NO
Range of Product	DPA

Complementary

Maximum Horse Power Rating	3 Hp 115 V AC, 1 phase 10 Hp 230 V AC, 1 phase 15 Hp 230 V AC, 3 phase 30 Hp 460 V AC, 3 phase 30 hp 575 V AC, 3 phase
Locked rotor rated current	300 A 277 V AC 250 A 460 V AC 200 A 575 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	440 V AC 50 Hz 480 V AC 60 Hz
Phase	3 phase
Electrical Connection	Quick connect terminals Box lugs
Height	4.1 in (105 mm)
Width	2.6 in (65 mm)
Depth	3.7 in (93 mm)

Environment

Product Certifications	UL Recognized[RETURN]CSA
------------------------	--------------------------

Ordering and shipping details

Category	US1CP1B21345
Discount Schedule	CP1B
GTIN	785901081128
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.700 in (6.858 cm)
Package 1 Width	3.800 in (9.652 cm)
Package 1 Length	4.300 in (10.922 cm)
Package 1 Weight	25.440 oz (721.212 g)

Unit Type of Package 2	CAR
Number of Units in Package 2	8
Package 2 Height	8.200 in (20.828 cm)
Package 2 Width	5.900 in (14.986 cm)
Package 2 Length	9.0000000000 in (22.86 cm)
Package 2 Weight	13.060 lb(US) (5.924 kg)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Approximate Dimensions

