



Single-Pole, 3-way Double Combination Switch, 15A 120/277V, Ivory.

## Features & Benefits

Easily accessible break-off separate or common feed.

Two devices fit into the space of one.

Tamper-resistant version features dual mechanical shutter system to help prevent insertion of foreign objects.

Side wire #12 and #14 AWG.

Grounding combination devices meet NEC Requirements.

For covering patents, see [www.legrand.us/patents](http://www.legrand.us/patents).

## Specifications

### General Info

Product Line	Pass & Seymour	Color	White
Finish	Satin	UPC Number	785007006230
Country Of Origin	Mexico	Features	Combination
Switch Type	Toggle	Number of Switches	2
Application Sector	Hospitality, Residential	Wall Plate Included	No
Standard	UL20	Warranty Type	1-Year Limited Warranty
Type	Combination, Switch, Tamper-Resistant		

### Dimensions

Product Width US	1.32 in	Product Depth US	0.94 in
------------------	---------	------------------	---------

---

Product Height US	4.06 in
-------------------	---------

---

### Listing Agencies / 3rd Party Agencies

---

cULus ListingNumber	140597	cULus Listed	Yes
---------------------	--------	--------------	-----

---

### Technical Information

---

Load Rating	15 A @ 120/277 VAC	Contact Configuration	N-0
-------------	--------------------	-----------------------	-----

---

Operating Cycles	30000	Connection Location	Side Only
------------------	-------	---------------------	-----------

---

Terminal Accommodation	#14 AWG - #12 AWG	Number of Gangs	1
------------------------	-------------------	-----------------	---

---

Throw Type	Single Throw	Amperage	15 A
------------	--------------	----------	------

---

Number of Poles	3-Way, Single Pole	Requires Neutral Wire	Yes
-----------------	--------------------	-----------------------	-----

---

Indoor/Outdoor	Indoor	Mounting Type	Wall Box
----------------	--------	---------------	----------

---

Wire Connection Type	Screw Terminals	Voltage	120 VAC, 277 VAC
----------------------	-----------------	---------	------------------

---

Load Type	CFL, Fluorescent, Halogen, Incandescent, LED, Universal, Xenon	Environmental Conditions	Flammability: UL94 V2
-----------	---	--------------------------	--------------------------

---