

# Product data sheet

Specifications

SQUARE D



## Mini circuit breaker, QO, 20A, 1 pole, 120/240VAC, 22kA, bolt on

QOB120VH

Product availability: Stock - Normally stocked in distribution facility

### Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	20 A
Voltage Rating	120/240 V AC 120 V AC
Mounting Type	Bolt-on
Number of Poles	1P
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Pressure plate

### Complementary

Interrupt Rating	22 kA 120/240 V AC 22 kA 120 V AC
Number of Panel Spaces	1
Wire Size	AWG 14...AWG 8 copper or aluminium
Tightening Torque	40.7 lbf.in (4.6 N.m)
Height	3.0 in (76 mm)
Width	0.7 in (19 mm)
Depth	2.9 in (74 mm)
Net Weight	0.300 lb(US) (0.136 kg)

### Environment

Certifications	UL Listed CSA
Ambient Rating	104 °F (40 °C)

### Ordering and shipping details

Category	US10DE200015
Discount Schedule	0DE2
GTIN	785901371731
Returnability	Yes
Country of origin	US

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	0.70 in (1.778 cm)
Package 1 Width	3.20 in (8.128 cm)
Package 1 Length	3.30 in (8.382 cm)
Package weight(Lbs)	4.800 oz (136.078 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	3.40 in (8.636 cm)
Package 2 Width	2.70 in (6.858 cm)
Package 2 Length	7.70 in (19.558 cm)
Package 2 Weight	2.851 lb(US) (1.293 kg)
Unit Type of Package 3	CAR
Number of Units in Package 3	100
Package 3 Height	8.10 in (20.574 cm)
Package 3 Width	7.70 in (19.558 cm)
Package 3 Length	17.00 in (43.18 cm)
Package 3 Weight	29.050 lb(US) (13.177 kg)

## Contractual warranty

Warranty	18 months
----------	-----------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 18

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic Yes

[EU RoHS Directive](#) Compliant

SCIP Number Af42fb01-813d-40c0-ae28-b8b3299dbc99

REACH Regulation [REACH Declaration](#)

Halogen content performance Halogen free product

## Use Again

### Repack and remanufacture


Circularity Profile No need of specific recycling operations

Take-back No

Technical Illustration

Dimensions

---



Dimensions are approximate. Refer to technical documentation for additional detail.

Image of product / Alternate images

Alternative

---

QO™  
QOB120VH  
**20A**  
120/240 VAC ~ 50/60Hz  
22,000 AIR/A nom.I

 **1** Pole  
Polo  
Pôle

 **Bolt-On**  
Atornillado  
Boulonné

