

24

Lever Bypass Meter Mains

320 Amps | 4 Terminals | Ringless | NEC 2020 Compliant



U6584-O-2/200-BL-NE



U6589-O-2/200-BL-NE

320 Amps | 4 Terminals | Ringless | Meter Mains | 1Ø

Catalog Number	Service	Hub	Connectors CU/AL		Bypass	Dimensions			Knockouts		
			Line	Load		D"	W"	H"	1	2	3
U6584-O-2/200-BL-NE	UG	Blank	3/8" x 16 Studs	#1/0-300	Lever	5¾	33	30	4	3	¼, ½
U6589-X-2/200 BL-NE	OH/UG	C.P.	3/8" x 16 Studs	#1/0-300	Lever	5¾	33	30	4	3	¼, ½

Notes

- **NEC 2020:** All products are NEC 2020 compliant.
- **Connectors:** The line wire section is supplied with ¾"-16 studs with hex head nuts and captive Belleville washers. For single lug connector kits, order **K1539** (350 kcmil) or **K1540** (600 kcmil). For twin lug connector kits, order **K1350** (350 kcmil).
- **Breakers:** The **U6584** and **U6589** are supplied with two Bolt-on Milbank **UQFBH-200** breakers.
- **Bypass:** The lever operates bypass device and supplies clamping action to meter spades.
- **Fifth terminals:** For field-installable fifth terminal, order catalog number **K3865**.



Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility, and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.