

Product data sheet

Characteristics

XVCTL1

Complete pre wired monolithic tower light, Harmony XVC, plastic, red orange green, 40mm, base mounting, steady, IP23, 24V AC DC



Main

Product or Component Type	Complete pre-wired monolithic tower light
Beacon or indicator bank unit type	3 illuminated units
Sound signalling	Buzzer
Mounting diameter	1.6 in (40 mm)
Device short name	XVC
Light source	LED steady or flashing red LED steady or flashing orange LED steady or flashing green
Supply circuit type	AC/DC

Complementary

Material	Polycarbonate: illuminated unit ABS (acrylonitrile butadiene-styrene): base unit PBT + ABS (UL94-V0): top cover SGP (chromium-plated): support tube
Mounting Location	On support tube, 17 mm
[Us] rated supply voltage	24 V
Cable cross section	0.0005 In ² (0.33 mm ²) 0.001 in ² (0.83 mm ²)
AWG Gauge	AWG 22 AWG 18
Cable length	17.7 in (450 mm)
Marking	CE
[Uimp] rated impulse withstand voltage	4 kV
Flashing frequency	1 Hz

Environment

Standards	IEC 60947-1 IEC 60947-5-1
Product Certifications	UL
Protective treatment	TC
Ambient Air Temperature for Storage	-31...158 °F (-35...70 °C)
Ambient Air Temperature for Operation	14...122 °F (-10...50 °C)
Overvoltage category	Class I IEC 61140
IP degree of protection	IP23 vertical surface installation IEC 60529

Ordering and shipping details

Category	US1IPOP22750
Discount Schedule	IPOP
GTIN	785901557234
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.100 in (23.114 cm)
Package 1 Width	2.300 in (5.842 cm)
Package 1 Length	5.400 in (13.716 cm)
Package 1 Weight	0.500 lb(US) (0.227 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.