

KAPO250R, Wire range: 2 -250 kcmil, Torque: 180-300 N lb.

By Burndy
Catalog # [KAPO250R](#)

250 kcmil AL MECH PIN ADAPTOR



Features

- AL9CU Dual Rated for both copper and aluminum conductor
- Listed to UL Wire Connector Standard UL486A-486B
- Rated for use with Fine Strand Conductor
- 600 Volt Rated
- Range Taking conductor port
- Plastisol insulated covers provided with each connector

Application

Terminate "upsized" conductor and/or fine strand conductor into mechanical connectors found in molded case circuit breakers, panel board equipment, and other switchgear.

Conductor

Conductor - Copper Str Size Range	2 AWG - 250 kcmil
Conductor - Copper Flex H Size Range	2 AWG - 250 kcmil
Conductor - Copper Flex I Size Range	2 AWG - 250 kcmil
Conductor - Copper DLO Size Range	2 AWG - 250 kcmil
Conductor - Copper Flex K Size Range	2 AWG - 250 kcmil
Conductor - AL Str Size Range	2 AWG - 250 kcmil
Conductor - Copper Str Run	#2 -250 kcmil
Conductor Size	2 AWG-250 KCMIL

Configuration

Connector Type Offset

Current

Amperage Rating 290
Voltage Rating 600 V

Dimensions

Outside Diameter 1.25
Width 1.43 in
Height 1.81 in
Length 2.47 in
Dimensions 2.47 in x 1.43 in x 1.81 in

General

Type

- 2 -250 kcmil Mechanical Pin Adaptor
- Off-Centered Pin

Material Aluminum
UPC 621945554153

Logistics

Carton Quantity 25
Pallet Quantity 2250

Product Assets

[Catalog \[English\]](#)