



Main

| | |
|-----------------------|--|
| Product | Miniature circuit-breaker |
| Range | QO |
| Current Rating | 20 A |
| Voltage Rating | 120 V AC |
| Mounting Type | Bolt-on |
| Number of Poles | 1P |
| Circuit Breaker Type | Combination ARC-fault and ground fault |
| Ratings | HACR rated |
| Electrical Connection | Pressure plate |
| Connections Terminals | Pigtail neutral |

Complementary

| | |
|------------------------|--|
| Interrupt Rating | 10 kA 120 V AC |
| Number of Panel Spaces | 1 |
| Wire Size | AWG 14...AWG 8 copper or aluminium AWG 14...AWG 10 copper |
| Tightening Torque | 35.4 lbf.in (4 N.m) |
| Height | 4.8 in (121 mm) |
| Width | 0.7 in (19 mm) |
| Depth | 2.9 in (74 mm) |
| Net Weight | 0.249 lb(US) (0.113 kg) |

Environment

| | |
|----------------|----------------------|
| Certifications | UL Listed[RETURN]CSA |
| Ambient Rating | 104 °F (40 °C) |

Ordering and shipping details

| | |
|-------------------|--------------|
| Category | US1DE2A06303 |
| Discount Schedule | DE2A |
| GTIN | 785901051251 |
| Returnability | No |
| Country of origin | MX |

Packing Units

| | |
|------------------------------|----------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 3.530 in (8.966 cm) |
| Package 1 Width | 0.742 in (1.885 cm) |
| Package 1 Length | 5.152 in (13.086 cm) |
| Package 1 Weight | 4.000 oz (113.398 g) |

Offer Sustainability

| | |
|----------------------------|--|
| California proposition 65 | WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |