

# Product data sheet

Specifications

SQUARE D



Contactor, Type S, multipole lighting, electrically held, 60A, 3 pole, 110/120VAC 50/60Hz coil, NEMA 1 [TAA]

8903SPG2V02

Product availability: Non-Stock - Not normally stocked in distribution facility

## Main

Product	Electrically Held Lighting Contactor
Type	S

## Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	60 A
Number of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Uden
Other Options	None
Electrical Connection	Lugs
Height	12.7 in (322 mm)
Depth	6.02 in (153 mm)
Width	7.8 in (198 mm)

## Environment

Enclosure Type	NEMA 1 painted sheet steel surface none
Product Certifications	UL Listed CSA

## Ordering and shipping details

Category	US10CP121325
Discount Schedule	0CP1
GTIN	785901619499
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

<b>Package 1 Height</b>	7.50 in (19.05 cm)
<b>Package 1 Width</b>	8.20 in (20.828 cm)
<b>Package 1 Length</b>	13.30 in (33.782 cm)
<b>Package weight(Lbs)</b>	12.240 lb(US) (5.552 kg)

---

## Compliance

---

Compliance TAA

## Contractual warranty

---

Warranty 18 months

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

 <b>Materials and Substances</b>	
Packaging made with recycled cardboard	<b>Yes</b>
Packaging without single use plastic	<b>No</b>
EU RoHS Directive	<b>Not compliant</b>

### Use Again

 <b>Repack and remanufacture</b>	
Take-back	<b>No</b>