

# EX225T6HCT

Transformer, dry type, DOE 2016, 225kVA,  
3 phase, 480V delta primary, 240V delta  
secondary, 25J, 150C rise, 120V ctr



## Main

Range of Product	Square D
Product or Component Type	Transformer
Device short name	DOE 2016
Transformer type	Energy efficient
Device Application	Low voltage electrical distribution

## Complementary

Box number	25J
Phase	3 phase
Rated operational power in VA	225 kVA
Network Frequency	60 Hz
Type of cooling	Natural convection
Primary Voltage	480 V delta
Number of tap-offs	2 2.5 % FCAN 4 2.5 % FCBN
Secondary voltage	240 V delta Centre tap 120 V
Coil Material	Aluminium
Basic IMP level (BIL)	10 kV
Temperature Rise	150 °C 220 °C insulated
DOE Efficiency	99.04 % at 35 % load factor , 167.000000000 °F (75.0 °C)
Sound Level	6 DB NEMA ST-20 49 dB
%IZ	4.2 %
%IX	0.0383 %
X/R Ratio	2.17
Let Through Current	12.8 kA
Transformer Losses	370.0 no load (core loss) 3970.0 load loss (coil loss)
Transformer BTU/HR	1635.7717302594401 16.6 % 2109.13027375 25 % 4649.0434749999995 50 % 8882.23214375 75 % 14808.696279999998 100 %
Height	57.5 in (1461 mm)
Depth	32.8 in (832 mm)
Width	40.08 in (1018 mm)
Net Weight	1450.004 lb(US) (657.71 kg)
Mounting support	Floor Floor, with 7400FMB

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Degree of protection	UL type 1 UL type 2, with 7400DS25J UL type 3R, with 7400WS25J
Electrical connection	4 Hole Nema Pad primary 0.4 in (11.1 mm) 6 Hole Nema Pad secondary 0.4 in (11.1 mm)

## Environment

Ambient Air Temperature for Operation	104 °F (40 °C)
Average ambient air temperature for operation	30 °C
Standards	UL 1561 CSA C22.2 No 47 NEMA ST-20

## Ordering and shipping details

Category	US1PE2X16251
Discount Schedule	PE2X
GTIN	785901750925
Returnability	No
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	57.52 in (146.1 cm)
Package 1 Width	40.08 in (101.8 cm)
Package 1 Length	32.8 in (83.2 cm)
Package 1 Weight	2061.35 lb(US) (935.01 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Approximate Dimensions

