

Description: 22 AWG 8/C STR CL2P, CMP, C(ETL)US FT6  
Compliance: UL Standards 13 & 444, NEC Articles 725 & 800, CSA C22.2 No. 214

#### Construction:

Conductor 22 AWG 7/.0096 Bare Copper  
Insulation Plenum PVC  
Color Blk,Wht,Red,Grn,Brn,Blu,Org,Ylw  
Thickness 0.007" nom.  
Diameter 0.044" nom.  
Lay Length 4.5" nom.

#### Jacket

Type Plenum PVC  
Color Natural  
Thickness 0.015" nom.  
Diameter 0.176" nom.

Legend (Ink Print) **HONEYWELL P/N 3107 8C22 3038058 (ETL) CL2P OR CMP C(ETL)US FT6 (RoHS)  
W/O# XXXXXX-XXXXXX XXXXX FT DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9**

#### Properties

Temperature Rating -20 to 60 °C  
Operating Voltage 300 Volts max.  
Capacitance 25 pf/ft nom.  
Impedance 85 Ohms nom.  
DC Resistance 16.5 Ohms/M' at 20°C  
Flame Rating NFPA 262, CSA C22.2 No. 2556 (FT6)