

-GENESIS-

Riser Rated Security & Control Cable Part Number: 2221

16 AWG 2 Stranded Conductors Shielded

Ratings CMR, CL3R, FPLR, FT4, Sunlight Resistant
Approvals ETL Listed

Construction

Conductor 16 AWG 19 Strand Bare Copper
Conductor Count 2
Insulation Polypropylene (0.007" nom.)
Insulation Colors Black, Red
Lay Length 3.00" nom.
Shielding Aluminum Foil/Mylar w/ 24 AWG Tinned-Copper Drain
Rip Cord Yes
Jacket PVC (0.017 " nom.)
Overall Diameter 0.180" nom.
Print Legend GENESIS P/N 2221 2C 16AWG SHIELDED 3038058 (ETL) CL3R OR FPLR OR CMR
C(ETL)US FT4 SUN RES 75C (RoHS) W/O# XXXXXX-XXXXXXX XXXXFT A B C D E F 1
2 3 4 5 6 7 8 9

Properties

Operating Voltage 300 Volts max.
DC Resistance 4.19 Ohms/1000' at 20°C
Capacitance 44.3 pF/ft. nom.
Impedance 34 Ohms nom.

Temperature -20°C to 75°C
Flame Rating UL 1666 (Riser); CSA C22.2 No. 2556 (FT4)
RoHS Compliant Yes

Country of Origin USA