

Product data sheet

Specifications

SQUARE D



Mini circuit breaker, Homeline, 15A, 1 pole, 120VAC, 10kA AIR, combo ARC/ground fault, plug on neutral, plug in, UL [TAA]

HOM115PDF

Product availability: Stock - Normally stocked in distribution facility

Main

Product	Miniature circuit-breaker
Range	Homeline
Current Rating	15 A
Certifications	UL Listed
Voltage Rating	120 V AC
Mounting Type	Plug-in
Number of Poles	1P
Short Circuit Current Rating	10 kA
Number of Spaces	1
Circuit Breaker Type	Combination ARC-fault and ground fault class A 6 mA
Ratings	HACR rated
Electrical Connection	Screw clamp terminals
Wire Size	1 x AWG 14...AWG 8 (aluminium/copper) 2 x AWG 14...AWG 10 (copper)

Complementary

Connections - Terminals	Plug-on neutral
Tightening torque	35.4 lbf.in (4.0 N.m) 0.004...0.009 in ² (2.5...6 mm ²) (AWG 14...AWG 8)
Height	3.13 in (79.50 mm)
Width	1 in (25.4 mm)
Depth	2.98 in (75.69 mm)

Environment

Ambient Air Temperature for Operation	104 °F (40 °C)
---------------------------------------	----------------

Ordering and shipping details

Category	US1DE3D06301
Discount Schedule	DE3D
GTIN	785901978510
Returnability	Yes
Country of origin	MX

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.400 in (3.556 cm)
Package 1 Width	3.900 in (9.906 cm)
Package 1 Length	5.100 in (12.954 cm)
Package weight(Lbs)	9.840 oz (278.959 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	40
Package 2 Height	4.200 in (10.668 cm)
Package 2 Width	13.800 in (35.052 cm)
Package 2 Length	21.000 in (53.340 cm)
Package 2 Weight	25.131 lb(US) (11.399 kg)

Contractual warranty

Warranty	Lifetime
----------	----------

