


Product data sheet

Specifications

SQUARE D



Contactor, Type S, multipole lighting, electrically held, 100A, 4 pole, 120/100VAC 60/50Hz coil, open style [TAA]

8903SQO3V02

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product	Electrically Held Lighting Contactor
Type	S

Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	100 A
Number of Poles	4P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Uden
Other Options	None
Electrical Connection	Lugs
Height	7.2 in (184 mm)
Depth	6.5 in (165 mm)
Width	9.8 in (248 mm)

Environment

Enclosure Type	Not rated (open device) surface none
Product Certifications	UL Listed CSA

Ordering and shipping details

Category	US10CP121325
Discount Schedule	0CP1
GTIN	785901861867
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 1 Height	8.50 in (21.59 cm)
Package 1 Width	11.40 in (28.956 cm)
Package 1 Length	13.60 in (34.544 cm)
Package weight(Lbs)	21.200 lb(US) (9.616 kg)

Compliance

Compliance TAA

Contractual warranty

Warranty 18 months


Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Not compliant

Use Again

 Repack and remanufacture	
Take-back	No