



Family

Catalog Number: PACOF-20B.50
Product ID: 7TAA292730R0005
UPC Number: 78620999799
EAN Number: 07630030270550
Status: Active

Divisible Flexible Black Conduit, (PACOF) Material - Polyamide 6, Conduit Size NW - 20, 50 Meters

- Can be opened and closed again in longitudinal directional any time
- PMA standard nominal widths can be used in combination with all PMA fittings
- Easy installation
- Trouble-free retrofitting
- Self-extinguishing
- Free from halogens and cadmium
- Vehicle Building

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5535 Electrical conduit
Brand Name	PMA
Type	Divisible Conduit
Application	Machine
Trade Size	NW20
Length	50 Meters
Flexibility	Medium Flexibility
Material	Polyamide/Nylon 6
Color	Black

European Specifications (ETIM)

ETIM	EC001175 Corrugated plastic hose
Nominal diameter	23mm
Outer diameter	24mm
Inner diameter	19mm
Material	Polyamide 6
Compressive strength	180N
Operating temperature	-40 - +105°C
Fire resistance in accordance with UL94	V0
UV resistant	Y
Colour	Black
Sheathing material	Not sheathed
Bending strength	Flexible
Lengthwise slotted	N
Closable (two-part)	Y
Halogen free	Y
Approved according to DIN EN 61386-23	N
Approved according to UR	N
Approved according to CSA	N
Approved according to LUL/British Standard	N
Approved according to Lloyd's Register TA	N
Approved according to UTAC	N
Approved according to DIN 5510	N
Approved according to NF F 16-101	N

Packaging

Inner Quantity	1
Outer Quantity	10
Outer Dimensions (inches)	47.244x31.496x30.709
Weight Uom	9.84 lbs. Each

Documents / Support Tools

Video US 1	Available on Website
------------	----------------------

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com