

YS2C, Cu Compression Splice, Long Barrel, 2 AWG

By Burndy
Catalog # [YS2C](#)



2 AWG, CU, Long Barrel SPLICE

Features

- Copper seamless barrel with center stop indentations to indicate when wire is fully inserted into each side of the barrel
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors clearly marked with color coding

Application

Wire Splice

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Wire Size	#2 AWG
Conductor - Copper Str Size	2 AWG
Conductor - Copper Str Navy Size	60 (37) Navy
Conductor Size	2 AWG
Conductor - Copper Str Size Range	2 AWG
Conductor Type	CODE

Configuration

Connector Type	LONG BARREL
----------------	-------------

Current

Voltage - Maximum	35000
Voltage Rating	35 kV

Dimensions

Package Length	0.000 in
Package Width	0.000 in
Package Weight	0.000 lb.
Dimension - L Length Overall mm	72 mm
Package Height	0.000 in
Dimension - Strip Length inch	1-5/16
Dimension - B Length inch	1.22 in
Dimension - Length Overall inch	2.82 in

General

Die Index	10
Trade Name	HYLINK™
Sub Brand	HYLINK
Color Code	Brown
Plated	Y
Feature - Barrel Type	Long
Feature - Barrel Style	Chamfered
Type	YS, Long Barrel
UPC 12 Digit	781810507001
UPC 14 Digit GTIN	00781810507001
Material	COPPER
Plating Type	Tin - Electro Plated
Finish Type	Tin-Plated
UPC	781810507001

Logistics

Minimum Pack Quantity	1
Carton Quantity	25

Product Assets

[Catalog \[English\]](#)