# Product data sheet

Specifications



## Main fusible (Class T) switch unit, EZ Meter-Pak, 1200A, 240VAC max, 3ph/4W, 1200A bus, UG, Type 3R, EUSERC

EZM31200FSE

**Product availability: Stock - Normally stocked in distribution facility**

## Main

| | |
|---|---|
| **Range of Product** | EZ meter-pak |
| **Product or Component Type** | Meter center main unit |
| **Main type** | Main Fusible Switch |
| **Included Items** | Main switch 1) 3P 1200 A 100 kA<br>Closing plate |

## Complementary

| | |
|---|---|
| **Main rated current** | 1200 A |
| **Bus rated current** | 1200 A |
| **Enclosure Material** | Painted steel |
| **[Ue] rated operational voltage** | 208Y/120 V AC<br>240/120 V delta AC |
| **Device mounting** | Surface |
| **Number of Phases** | 3 phase in<br>3 phase out |
| **Service feed location** | UG |
| **Electrical connection** | Lugs 1 AWG 6...300 kcmil aluminium/copper) ground<br>Studs 3line<br>Studs 3neutral |
| **Wiring configuration** | 4-wire |
| **Height** | 66.20 in (1681.48 mm) |
| **Width** | 32.39 in (822.71 mm) |
| **Depth** | 13.69 in (347.73 mm) |

## Environment

| | |
|---|---|
| **Product Certifications** | UL Listed<br>EUSERC |
| **Enclosure Rating** | NEMA 3R |

## Ordering and shipping details

| | |
|---|---|
| **Category** | US10DE400020 |
| **Discount Schedule** | 0DE4 |
| **GTIN** | 00785901939405 |
| **Returnability** | Yes |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Country of origin** | MX |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 26.00 in (66.040 cm) |
| **Package 1 Width** | 42.60 in (108.204 cm) |
| **Package 1 Length** | 75.80 in (192.532 cm) |
| **Package weight(Lbs)** | 453.000 lb(US) (205.477 kg) |

## Contractual warranty

| | |
|---|---|
| **Warranty** | 18 months |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Carbon footprint (kg CO2 eq, Total Life cycle) | 1581 |
| Environmental Disclosure | Product Environmental Profile |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | No |
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant with Exemptions |
| REACh Regulation | REACh Declaration |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Circularity Profile | No need of specific recycling operations |
| Take-back | No |