

FC70: Bus Drop, Closed Mesh, Single Eye, Cable Diameter 0.70 - 0.85 inches, Bale Length 9-in, Mesh Length 8.5-in, Break Strength 1900 lbs.



Features & Benefits

Bus drop grips are used as cable support. They relieve any direct tension from the critical connection and absorb vibration and flexing.

Bus drop grips are woven of galvanized steel wire.

They are offered with either the single eye or locking bale attachment.

Support grips are woven of corrosion-resistant tinned-stainless steel wire.

Most Flexcor products have UL and/or CSA approvals. Please contact factory for approval information.

Bale Length: 9: Mesh Length: 8.5

Specifications

General Info

Product Line	Pass & Seymour	UPC Number	785007998740
Country Of Origin	Mexico	Construction	Support and Strain Relief Grips, Various Types of Pulling
Application Sector	Industrial	Standard	UL/CSA Approval (consult factory)

Dimensions

Product Width US	0.85 in	Product Length US	8.5 in
------------------	---------	-------------------	--------

Listing Agencies / 3rd Party Agencies

CSA Listed	Yes	CSA File Number	67507
------------	-----	-----------------	-------

Technical Information

Maximum Cable Range	0.7 in	Minimum Cable Range	0.85 in
Capacity	Various Cable Diameter Ranges	Mounting	Consult the Factory for Mounting Recommendations
Load	Approx. Break Strength: 1900		